

Outdoor Housing for Panasonic PTZ Cameras

Modular Outdoor Housing Solution
By KST Moschkau GmbH



KEY FEATURES

- Designed exclusively for Panasonic PTZ cameras
- Protection Class IP 64 Standard for work in tough environments
- Active heating and ventilation
- Temperature range between -20°C and +40°C
- Air inlet and outlet protected by dust -and insect- filter

KST Moschkau GmbH has developed an outdoor housing solution for Panasonic PTZ cameras. It provides maximum protection against environmental influences such as dust, smog, salt, moisture and insects.

The outdoor housing can be used for various Panasonic PTZ camera series as it is available in two versions. Its modular design is available in configurations with HD-SDI and HDMI output as well as IP streaming. Both versions are available with transparent or smoked dome.

The outdoor housing holds the camera, lens and pan/tilt mechanism clean and dry and is including heating and ventilation systems, supporting a temperature range from -20°C to +40°C.

- Protection Class IP64 standard
- Temperature range between -20°C and +40°C assured by active heating and ventilation
- Expanded temperature range between -40°C and +60°C by additional, enhanced heating and ventilation
- Available in configurations with HD SDI and HDMI output, IP streaming and POE supply of camera module and system temperature conditioning
- Power-connection : 230 VAC, alt. 12 VDC or POE

- Signal-connection : SDI/HDSDI out (or HDMI), optional CVBS out, Genlock in, LAN
- Remote-connection : LAN, optional RS422
- Length of the cable-set : 2,5 m from mounting base (optional special lengths, connectors in bracket or junction boxes for outdoor installation)

Optional:

Wall bracket fitted with ceiling, pole mount or special mount if requested

Integrated Fiber Transmission

For AW-UE70/-UN70, AW-HE42/-HN42, AW-HE40/-HN40 & AW-HE38/-HN38 series:

• KST-OH70WM-S	Outdoor Housing with Wall Mount (SDI)
• KST-OH70WM-H	Outdoor Housing with Wall Mount (HDMI)
• KST-OH70WM-POE	Outdoor Housing with Wall Mount (PoE)
• KST-OH70WM-F	Outdoor Housing with Wall Mount (Fiber)
• KST-OH70CM-S	Outdoor Housing with Ceiling Mount (SDI)
• KST-OH70CM-H	Outdoor Housing with Ceiling Mount (HDMI)
• KST-OH70CM-POE	Outdoor Housing with Ceiling Mount (PoE)
• KST-OH70CM-F	Outdoor Housing with Ceiling Mount (Fiber)

For AW-UE150 & AW-HE130/-HN130 series:

• KST-OH150WM-S	Outdoor Housing with Wall Mount (SDI)
• KST-OH150WM-H	Outdoor Housing with Wall Mount (HDMI)
• KST-OH150WM-POE	Outdoor Housing with Wall Mount (PoE)
• KST-OH150WM-F	Outdoor Housing with Wall Mount (Fiber)
• KST-OH150CM-S	Outdoor Housing with Ceiling Mount (SDI)
• KST-OH150CM-H	Outdoor Housing with Ceiling Mount (HDMI)
• KST-OH150CM-POE	Outdoor Housing with Ceiling Mount (PoE)
• KST-OH150CM-F	Outdoor Housing with Ceiling Mount (Fiber)

For the AW-UE100 series:

• KST-OH100WM-S	Outdoor Housing with Wall Mount (SDI)
• KST-OH100WM-H	Outdoor Housing with Wall Mount (HDMI)
• KST-OH100WM-POE	Outdoor Housing with Wall Mount (PoE)
• KST-OH100WM-F	Outdoor Housing with Wall Mount (Fiber)
• KST-OH100CM-S	Outdoor Housing with Ceiling Mount (SDI)
• KST-OH100CM-H	Outdoor Housing with Ceiling Mount (HDMI)
• KST-OH100CM-POE	Outdoor Housing with Ceiling Mount (PoE)
• KST-OH100CM-F	Outdoor Housing with Ceiling Mount (Fiber)

SPECIFICATIONS

URL: https://business.panasonic.it/telecamere-professionali/custodia_per_esterni/kst-oh70-xyz

CONTACT

Web: <https://business.panasonic.it/telecamere-professionali/contact-us>